

# SÄKERHETSVENTILER

## Mässing

---

Avblåsningskapacitet vid 1 0% över öppningstrycket

Luft, Nm<sup>3</sup>/h

Öppningstryck, bar	DN08	DN1 0	DN1 5	DN20	DN25
0, 2	20	35	46	1 00	1 33
0, 3	25	45	54	1 1 9	1 44
0, 4	29	52	67	1 37	1 67
0, 5	32	58	74	1 58	1 85
0, 6	35	64	82	1 72	21 1
0, 7	37	70	87	1 87	235
0, 8	41	74	95	200	260
0, 9	43	80	1 01	21 3	282
1, 0	46	85	1 07	227	305
1, 5	60	1 08	1 37	286	408
2, 0	73	1 32	1 66	346	506
3, 0	1 00	1 82	222	465	699
4, 0	1 25	228	279	584	889
5, 0	1 51	274	336	703	1 070
6, 0	1 76	321	393	821	1 251
7, 0	201	367	450	940	1 432
8, 0	227	41 4	507	1 059	1 61 3
9, 0	252	460	564	1 1 78	1 794
1 0, 0	278	507	621	1 297	1 975
1 1, 0	303	553	678	1 41 6	21 56
1 2, 0	329	599	735	1 535	2337
1 3, 0	354	646	791	1 654	251 8
1 4, 0	380	692	848	1 773	2700
1 5, 0	405	739	905	1 891	2881
1 6, 0	431	785	962	201 0	3062
1 7, 0	456	832	1 01 9	21 29	3243
1 8, 0	482	878	1 076	2248	3424
1 9, 0	507	925	1 1 33	2367	3605
20, 0	533	971	1 1 90	2486	3786
21, 0	558	1 01 7	1 247	2605	3967
22, 0	584	1 064	1 304	2724	41 48
23, 0	609	1 1 1 0	1 361	2843	4329
24, 0	635	1 1 57	1 41 7	2961	451 0
25, 0	660	1 203	1 474	3080	4691
26, 0	685	1 250	1 531	31 99	4872
27, 0	71 1	1 296	1 588	331 8	5053
28, 0	736	1 342	1 645	3437	5234
29, 0	762	1 389	1 702	3556	541 5
30, 0	787	1 435	1 759	3675	5597
31, 0	81 3	1 482	1 81 6	3794	5778
32, 0	838	1 528	1 873	391 3	5959
33, 0	864	1 575	1 930	4031	61 40
34, 0	889	1 621	1 986	41 50	6321
35, 0	91 5	1 667	2043	4269	6502
36, 0	940	1 71 4	21 00	4388	6683
37, 0	966	1 760	21 57	4507	6864
38, 0	991	1 807	221 4	4626	7045
39, 0	1 01 7	1 853	2271	4745	7226
40, 0	1 042	1 900	2328	4864	7407
41, 0	1 068	1 946	2385	4983	7588
42, 0	1 093	1 993	2442	51 01	7769
43, 0	1 1 1 9	2039	2499	5220	7950
44, 0	1 1 44	2085	2556	5339	81 31
45, 0	1 1 70	21 32	261 2	5458	831 3
46, 0	1 1 95	21 78	2669	5577	8494
47, 0	1 220	2225	2726	5696	8675
48, 0	1 246	2271	2783	581 5	8856
49, 0	1 271	231 8	2840	5934	9037
50, 0	1 297	2364	2897	6053	921 8

---