

Microprocessor controlled MIG-MAG/FLUX/BRAZING inverter wire welding machine. Technomig is confirmed as the perfect solution for a wide range of applications, from maintenance to installation, because of its flexibility and the different materials it can weld (steel, stainless steel, aluminium). The fast SYNERGIC adjustment of the welding parameters thanks to the "ONE TOUCH" technology, makes the product very easy to use. Just set the material thickness and start welding; the intelligent and automatic control of the arc, moment by moment, maintains high welding performance in all working conditions, with different materials and/or gases. The operator can also intervene manually along the arc length: this adjustment means the weld seam can be modified according to the welder's style. Lightweight and very compact, Technomig can be moved around easily in all intervention areas, both indoors and outdoors. Main features: polarity change for GAS MIG-MAG/BRAZING welding * synergic adjustment with setting only of the material thickness * fine adjustment of the arc length * 10 synergy curves available * compact and light * thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections. Fit for NO GAS/Flux welding, it can be transformed into MIG-MAG with the optional kit. Complete with MIG-MAG torch, work clamp and cable.



PROFESSIONAL



LIKE AN ENDLESS ELECTRODE

FLUX

WELDS FE,SS,AL,GALVANISED SHEETS

MIG-MAG

EASY TO USE, COMPACT AND LIGHT

EASY

10 PRE-SET SMART CURVES

SYNERGY

SEAM CAN BE SHAPED AS REQUIRED

FINE SET

Norms: LVD: EN 60974-1 EMC: EN 60974-10

V_{ph} V50/60Hz	A_{MIN} A_{MAX} A	A_{MAX} 40°C EN60974-1	A_{60%} 40°C EN60974-1	V_o V	A_{60%} A _{MAX} A	P_{60%} MAX kW	η n%	cosφ cosphi	ST mm
230 1 ph	20 150 DC	115 20% DC	65 DC	50	8,7 20	1,2 2,8	86	0,7	0,6 0,8
SS mm	AL mm	FX mm	BZ mm	IP	W_L cm(L,W,H)	kg kg	BAR CODE	pz/pallet	pz/pallet - B
0,8	0,8 1	0,8 1,2	0,8	IP23	46 X 24 X 36	10,1	8004897883 26 7	18	12